



SUMMERS[®]

COULTER-CHISEL



Watch a video of the
Coulter-Chisel

HEAVY RESIDUE?

Introducing the Summers COULTER-CHISEL

Featuring Summers Field Tested Tough:

- 22" Diameter x .256" Thickness Gang Mounted Coulter Blades on 12" spacing, to size residue. Your Choice of 13 Wave, Flat or Turbo Blade Design.
- Four Ranks of 700# Trip Pressure Chisel Shanks on 12" spacing (1050# Trips Optional on up to 36' machines), to handle your toughest field conditions.
- Model 106 Mounted Harrow, to level the soil and evenly distribute crop residue.

FIELD TESTED TOUGH




The floating hitch and tricycle wheel arrangement on 32', 36' and 40' machines provide more consistent penetration depth. 10" stroke rephasing cylinders provide positive depth control and ample transport clearance.



Working Width	Transport Width	Hitch Design	Engine HP RQRD
32'	19'2"	Floating	320-448
36'	19'2"	Floating	360-504
40'	19'2"	Floating	400-560

Telephone (701) 438-2855
 Web Site: www.summersmfg.com

In a continuing desire to improve its products, Summers Manufacturing Company, Inc. reserves the right to change design, materials, and/or specifications without notice or obligation.



SUMMERS

Manufacturing Company, Inc.
 Devils Lake and Maddock ND 58348